

IN THE CLAIMS:

Please amend claims 1, 2, 5, 6, 7, 12, 13, 15, 18, 19, and 20 as follows.

1. (Currently Amended) A system for providing secure mobile connectivity that implements Mobile IP Home Agent functionality via distributed components, comprising:

a mobile node belonging to a home network located within a secure network, the mobile node having a network interface configured to communicate with other nodes, the mobile node having only one security association and only one mobility binding with a ~~Home Agent~~home agent (HA) for the ~~Mobile-mobile IP Home Agent~~home agent functionality;

a ~~Proxy Home Agent~~proxy home agent (PHA) connected to the home network and located within the secure network, wherein the PHA is configured to provide a proxying functionality;

the HA located outside of the secure network, wherein the HA is configured to provide a signaling and tunneling functionality and to notify the PHA of the mobile node; and

a virtual private network (VPN) gateway located outside the secure network and configured to work in conjunction with the HA.

2. (Currently Amended) The system of Claim 1, wherein the VPN gateway and the HA are located within a single device within a demilitarized zone (DMZ).

3. (Original) The system of Claim 1, further comprising a firewall coupled to the secure network and the VPN gateway; wherein the HA is located within the firewall.

4. (Original) The system of Claim 1, wherein the HA is a separate device from the VPN gateway.

5. (Currently Amended) The system according to claim 1, further comprising:
a demilitarised zone (DMZ) located outside the secure network, wherein the VPN gateway and the HA reside in the DMZ; a first firewall between the secure network and the DMZ; a second firewall between the DMZ and an external network configured to deny communications from the external network with a source address in the known range; and wherein the mobile node has a permanent address in a known range.

6. (Currently Amended) The system according to claim 1, further comprising:
a demilitarised zone (DMZ) located outside the secure network, wherein the VPN gateway and the home agent reside in the DMZ; a first firewall between the secure network and the DMZ; wherein the mobile node has a permanent address in a known range and the first firewall is programmed to deny all communications from the DMZ with a source address in the known range; and wherein the VPN gateway has a direct connection to an internal interface of the first firewall such that the first firewall considers the VPN gateway transmitted data as internal to the secure network.

7. (Currently Amended) The system of Claim 1, further comprising a demilitarised zone (DMZ) comprising a first router coupled to a second router that is coupled to a firewall, the

VPN gateway coupled to the first router and the firewall; the HA coupled to the first router.

8. (Previously Presented) The system of Claim 7, wherein packets from the mobile node destined toward nodes inside the secure network first go the HA and then to the VPN gateway that is configured to forward the packets through the firewall to the secure network.

9. (Original) The system of Claim 8, wherein packets from the second router to the firewall having a source address in a known range are dropped by the firewall.

10. (Previously Presented) The system according to claim 1, wherein a router is directly connected to a firewall and the VPN gateway and the HA connect to a different interface of the router and the firewall.

11. (Original) The system of Claim 10, wherein the firewall is configured such that it considers the interface with which it connects to the VPN gateway as an internal interface and packets with a source address that are outside of a known address range received on the internal interface are dropped, and packets with a source address that are within the known address range that are received by the firewall on an external interface are dropped.

12. (Currently Amended) The system of Claim 11, wherein VPN encapsulated packets are forwarded to the VPN gateway and when a ~~Security Association~~security association

(SA) exists, the packet is decrypted and forwarded to the firewall on the internal interface and when a SA does not exist the packet is dropped.

13. (Currently Amended) The system of Claim 12, wherein ~~Mobile~~mobile IP packets and VPN encapsulated packets first reach the ~~Home Agent~~home agent which are forwarded to the VPN gateway and then to the secure network through the firewall's internal interface.

14. (Previously Presented) The system of Claim 1, further comprising a firewall coupled to the secure network and the VPN gateway; and a router includes an access control list used to drop packets that have a source address that belong to a known address range.

15. (Currently Amended) A method for secure communication between a mobile node associated with a home network in a secure network and a correspondent node;
comprising:

establishing a ~~Proxy Home Agent~~proxy home agent (PHA) located within the secure network to monitor data directed to the mobile node;

establishing a ~~Home Agent~~home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the PHA of the mobile node;

collecting data directed to the mobile node;

packaging the collected data in a virtual private network (VPN) secure tunnel to an internal address of the mobile node to create VPN packaged data; and

tunneling the VPN packaged data to a current address of the mobile node.

16. (Original) The method of claim 15, wherein the VPN secure tunnel follows the IP security protocol.

17. (Original) The method of claim 15, wherein the tunneling of the VPN packaged data to the external mobile node occurs according to the IP mobility protocol.

18. (Currently Amended) The method of Claim 15, further comprising: packaging the collected data in an IP-in-IP tunnel and sending it to a VPN device for VPN encryption and tunneling the VPN packaged data to the current address of the ~~Mobile~~mobile node.

19. (Currently Amended) A system for secure mobile connectivity that implements ~~Mobile-mobile~~ IP Home Agent~~home agent~~ functionality via distributed components; comprising:

means for establishing a ~~Proxy Home Agent~~proxy home agent (PHA) located within a secure network to monitor data directed to a mobile node;

means for establishing a ~~Home Agent~~home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the PHA of the mobile node;

means for collecting data directed to the mobile node;

means for packaging the collected data in a virtual private network (VPN) secure tunnel to an internal address of the mobile node to create VPN packaged data;

means for tunneling the VPN packaged data to a current address of the mobile node;

means for the ~~Home Agent~~home agent to communicate to the PHA that the mobile node has moved outside its home network;

means for the ~~Home Agent~~home agent to communicate to the PHA that the mobile node has come back to its home network; and

means for enabling the PHA to create and remove a proxy address resolution protocol (ARP) entry for a permanent address associated with the mobile node.

20. (Currently Amended) A computer program embodied on a computer readable medium, the computer program being configured to control a processor to perform~~computer software product comprising instructions that cause an electronic device to perform;~~

establishing a proxy home agent (PHA) located within a secure network to monitor data directed to a mobile node;

establishing a home agent configured to create only one security association with the mobile node and only one mobility binding with the mobile node and to notify the PHA of the mobile node;

collecting data directed to the mobile node;

packaging the collected data in a virtual private network (VPN) secure tunnel to an internal address of the mobile node to create VPN packaged data; and

tunneling the VPN packaged data to a current address of the mobile node~~the actions of~~

Claim 15.